



## ITEM NO. G2000

### IP Version Emergency Phone Box

#### DESCRIPTION

1. Metall body, solid and temperature bearable
2. Handset free
3. Heavy duty Vandal resistant buttons.
4. With or without keypad optional
5. Lightning protection standard to ITU-T K21
6. Waterproof grade about IP65
7. Body with grounding connection protection
8. Support hotline call, self stop if the other side hang up.
9. Built-in loud speaker, noise canceling microphone
10. AC 110v/220v powered or built-in rechargeable battery with solar powered panel optional
11. The design is super thin and smart. Embed style and hanging style can be chosen.
12. Time out function optional
13. Colours: RED + Stainless steel , If the qty over 100pcs can be To customer specification



## **SPECIFICATION**

Ringling: Through internal Speaker/ringer  
Power Supply: Re-chargeable Battery powered: 11.1V/14Ah, Solar back-up: 12V/30W  
Time out: selectable 0-20 minutes  
Temperature: -20°C~ +60°Cemp  
Relative Humidity: up to 90%  
Built-in battery Standby: 3 days  
Built-in battery talking time: 18 hours  
Auxiliary Contacts:1 Aux Output, dry contact  
Contact Ratings. Load: Resistive load  
Rated load:0.3 A at 125 VAC; 1 A at 30 VDC  
Rated carry current:1A  
Audio Codes:G.711, G.722, G.729  
Network:10/100 BaseTX Ethernet, RJ45 connectors, Cat5e or better  
IP Protocols:IPv4, TCP, UDP, DHCP, SIP  
LAN Protocols:Power over Ethernet(PoE,802.3af), WLAN(IEEE 802.3af), Network Access Control(IEEE 802.1x),STP(IEEE 802.1d), RSTP(IEEE 802.1d-2004)  
Programming:Non-volatile flash memory programming and configuration through Web GUI  
Management and Operation:DHCP and static IP, remote automatic software upgrade, centralized monitoring.  
Echo cancellation code:G.167/G.168  
Environment conditions:  
Ambient temperature: -40°C to 70°C. Relative humidity:10%~95%  
Atmospheric pressure: 86~106Kpa Circumstance noise:less than 60dB(A)  
Impact protection: IK 09 according to EN50102

## **CERTIFICATION**



RCM: AS/NZS CISPR 32      Australian communications:AS/CA S004  
Australian Equipment-safety: AS/NZS 60950.1:2015  
EMC: EN50121(Railway application-Electromagnetic Compatibility)

## **PACKAGING**

Telephone Unit size: 2200\*310\*255mm Unit Net weight: 90kg  
2pcs in a wooden box CTN box, size: 35X80X255 G.W: 186kg  
20GP: 88PCS 40GP: 176PCS 40HQ: 205PCS

